


NAM

圓線彈簧(內徑標準型, 40%壓縮量)



內徑 D  $\phi$  8.5以下( $\pm 0.3$ mm)  
 $\phi$  10.6以上( $\pm 0.4$ mm)  
 自由長 L 50mm以下( $\pm 1$ mm)  
 60mm以上( $\pm 2$ mm)

Ma. 材質 SWP-A

梢徑	品號	D <sub>1</sub>	D	d	L	F	密著長	定數	F=L×32%	單價
		外徑	內徑	線徑	自由長				荷重	
		mm	mm	mm	mm				N(max)	
5	NAM 5.5-30	7.3	5.5	0.9	30	9.6	13.1	2.1	20.6	•
	35				11.2	14.9	1.8			
	40				12.8	16.2	1.6			
	45				14.4	18.0	1.4			
	50				16.0	19.8	1.3			
6	NAM 6.5-30	8.5	6.5	1.0	30	9.6	14.0	2.1	20.6	•
	35				11.2	15.5	1.8			
	40				12.8	17.5	1.6			
	45				14.4	19.5	1.4			
	50				16.0	21.0	1.3			
8	NAM 8.5-30	10.7	8.5	1.1	30	9.6	9.4	2.9	27.5	•
	35				11.2	10.5	2.5			
	40				12.8	11.6	2.1			
	45				14.4	12.7	1.9			
	50				16.0	13.8	1.7			
	60				19.2	16.0	1.4			
10	NAM 10.6-30	13.2	10.6	1.3	30	9.6	11.4	2.9	27.5	•
	35				11.2	12.7	2.5			
	40				12.8	14.0	2.1			
	45				14.4	15.3	1.9			
	50				16.0	16.6	1.7			
	60				19.2	19.2	1.4			
13	NAM 13.6-35	16.8	13.6	1.6	35	11.2	14.4	3.1	34.3	•
	40				12.8	15.6	2.7			
	45				14.4	17.2	2.4			
	50				16.0	18.4	2.1			
	60				19.2	20.8	1.8			
16	NAM 16.6-35	20.2	16.6	1.8	35	11.2	15.3	3.1	34.3	•
	40				12.8	16.7	2.7			
	45				14.4	18.5	2.4			
	50				16.0	19.4	2.1			
	60				19.2	22.5	1.8			

• 荷重(N)=定數(N/mm)×壓縮量(mm)

• NAM☒部兩端研磨

• 密著長是參考值, 製作時會有少許差異

• 1N=0.101972Kg f · 耐熱溫度80°C

訂貨方式:  交期:  天

NAM5.5-30