


OF

不銹鋼圓線彈簧

SUS  
防銹

外徑 D  $\phi$  10以下  $0_{-0.5}^0$ mm  
 $\phi$  12以上  $0_{-0.8}^0$ mm  
 自由長 L 50以下  $\pm 1.5$ mm  
 55以上  $\pm 2.5$ mm



Ma. 材質 不銹鋼  
 Co. 顏色 本色

D \ Type	OR	OF	OL	OM	OH
3					
4					
5				N/mm 1.96	N/mm 2.94
6	N/mm	N/mm	N/mm	N/mm	N/mm
8	0.29	0.49	0.98	2.94	5.88
10					
13					N/mm 9.80
16					N/mm 14.7
20	N/mm 0.49	N/mm 0.98	N/mm 2.94	N/mm 4.90	N/mm 9.80
F MAX	F=L×60%	F=L×45%	F=L×40%	F=L×Fa%	F=L×Fa%

OF: Fmax (容許壓縮量)=L×45%

品號	d	密著長	F	荷重	單價
Type D - L	mm	mm	max	N/max	
OF02-05*	0.2	2.35	2.25	0.66	
10*	0.2	2.35	4.5	1.3	
15*	0.26	7.8	6.7	2.0	
20*	0.26	7.8	9.0	2.7	
25*	0.29	13.6	11.2	3.3	
30*	0.29	13.6	13.5	4.0	
OF03-05*	0.26	1.8	2.25	1.1	
10*	0.32	3.5	4.5	2.2	
15*	0.32	3.5	6.7	3.2	
20*	0.35	6.3	9.0	4.4	
25*	0.35	6.3	11.2	5.5	
30*	0.4	12.4	13.5	6.6	
35*	0.4	12.4	15.7	7.6	
40*	0.4	12.4	18.0	8.8	
OF04-05*	0.32	2.0	2.25	1.1	
10*	0.35	3.0	4.5	2.2	
15*	0.4	5.2	6.7	3.2	
20*	0.4	5.2	9.0	4.4	
25*	0.45	9.5	11.2	5.5	
30*	0.45	9.5	13.5	6.6	
35*	0.5	15.5	15.7	7.6	
40*	0.5	15.5	18.0	8.8	
45*	0.5	15.5	20.0	9.8	

品號	d	密著長	F	荷重	單價
Type D - L	mm	mm	max	N/max	
OF04-50*	0.5	15.5	22.5	10.8	
60*	0.55	22.6	27.0	12.7	
OF05-05*	0.35	2.01	2.25	1.1	
10*	0.4	3.2	4.5	2.2	
15*	0.4	3.2	6.75	3.3	
20*	0.45	4.95	9.0	4.4	
25*	0.45	4.95	11.25	5.5	
30*	0.5	7.75	13.5	6.7	
35*	0.5	7.75	15.75	7.7	
40	0.6	19.5	18.0	8.8	
45	0.6	19.5	20.25	10.0	
50	0.6	19.5	22.5	11.2	
60	0.65	27.95	27.0	13.4	
OF06-05*	0.4	2.2	2.25	1.1	
10*	0.5	5.0	4.5	2.2	
15*	0.55	7.7	6.7	3.2	
20*	0.55	7.7	9.0	4.4	
25	0.6	10.8	11.2	5.5	
30	0.65	15.6	13.5	6.6	
35	0.65	15.6	15.7	7.6	
40	0.65	15.6	18.0	8.8	
45	0.65	15.6	20.0	9.8	
50	0.7	23.1	22.5	10.8	

OF

## 不銹鋼圓線彈簧

品號	d	密著長 mm	F max	荷重 N/max	單價	品號	d	密著長 mm	F max	荷重 N/max	單價
Type D - L						Type D - L					
OF06-60	0.7	23.1	27.0	12.7	•	OF13-15	0.8	5.6	6.7	3.2	
70	0.75	30.8	31.5	14.7		20	0.8	5.6	9.0	4.4	
OF08-10	0.6	4.2	4.5	2.2	•	25	0.85	7.2	11.2	5.5	
15	0.65	7.2	6.7	3.2		30	1.0	14.0	13.5	6.6	
20	0.7	10.5	9.0	4.4	•	35	1.0	14.0	15.7	7.6	•
25	0.7	10.5	11.2	5.5		40	1.0	14.0	18.0	8.8	
30	0.75	13.5	13.5	6.6	•	45	1.1	21.5	20.0	9.8	
35	0.75	13.5	15.7	7.6		50	1.1	21.5	22.5	10.8	
40	0.8	18.4	18.0	8.8	•	60	1.1	21.5	27.0	12.7	•
45	0.8	18.4	20.0	9.8		70	1.2	30.0	31.5	14.7	
50	0.8	18.4	22.5	10.8	•	80	1.2	30.0	36.0	17.7	
60	0.85	26.4	27.0	12.7		OF16-15	0.9	5.6	6.7	3.2	
70	0.85	26.4	31.5	14.7	•	20	1.0	7.7	9.0	4.4	•
80	0.85	26.4	36.0	17.7		25	1.0	7.7	11.2	5.5	
OF10-10	0.65	4.6	4.5	2.2	•	30	1.1	12.1	13.5	6.6	•
15	0.65	4.6	6.7	3.2		35	1.1	12.1	15.7	7.6	
20	0.8	9.6	9.0	4.4	•	40	1.2	18.0	18.0	8.8	
25	0.8	9.6	11.2	5.5		45	1.2	18.0	20.0	9.8	
30	0.85	12.8	13.5	6.6	•	50	1.2	18.0	22.5	10.8	•
35	0.85	12.8	15.7	7.6		60	1.3	26.0	27.0	12.7	
40	0.9	17.0	18.0	8.8	•	70	1.3	26.0	31.5	14.7	•
45	0.9	17.0	20.0	9.8		80	1.4	35.0	36.0	17.7	
50	0.9	17.0	22.5	10.8	•	OF20-20	1.2	7.2	9.0	8.8	•
60	1.0	28.0	27.0	12.7		25	1.3	9.1	11.3	11.1	
70	1.0	28.0	31.5	14.7	•	30	1.4	11.9	13.5	13.2	•
80	1.0	28.0	36.0	17.7		35	1.4	11.9	15.8	15.5	
OF12-15	0.8	6.8	6.7	3.2	•	40	1.5	15.8	18.0	17.7	•
20	0.8	6.8	9.0	4.4		45	1.5	15.8	20.3	19.9	
25	0.8	6.8	11.2	5.5	•	50	1.6	20.8	22.5	22.1	•
30	0.9	10.8	13.5	6.6		60	1.6	20.8	27.0	26.5	
35	1.0	17.0	15.7	7.6	•	70	1.7	26.4	31.5	30.9	•
40	1.0	17.0	18.0	8.8		80	1.7	26.4	36.0	35.3	
45	1.0	17.0	20.0	9.8	•	• 荷重(N)=定數(N/mm)×壓縮量(mm) • 密著長是參考值,製作時會有少許差異 • ★記號兩端皆不研磨。 • 耐熱溫度80°C • 1N=0.101972Kgf。					
50	1.1	26.4	22.5	10.8							
60	1.1	26.4	27.0	12.7	•						
70	1.1	26.4	31.5	14.7							
80	1.2	39.6	36.0	17.7	•						

訂貨方式: 品號 交期: 1 天

OF08-30