


NA L

圓線彈簧 (內徑標準型, 40%壓縮量)



內徑 D φ 8.5以下(±0.3mm)  
φ 10.6以上(±0.4mm)

自由長 L 50mm以下(±1mm)  
60mm以上(±2mm)

Ma 材質 SWP-A

梢徑	品號 Type D - L	D <sub>1</sub>	D	d	L	F max	密著長 mm	定數 N/mm	F=L×40%	單價
		外徑 mm	內徑 mm	線徑 mm	自由長 mm				荷重 N(max)	
5	NAL 5.5-30	7.0	5.5	0.75	30	12	10.9	1.1	13.7	.
	35				14	12.0	1.0			
	40				16	13.5	0.9			
	45				18	15.0	0.8			
	50				20	16.5	0.7			
6	NAL 6.5-30	8.1	6.5	0.8	30	12	9.6	1.1	13.7	.
	35				14	10.8	1.0			
	40				16	12.0	0.9			
	45				18	13.2	0.8			
	50				20	14.4	0.7			
8	NAL 8.5-30	10.5	8.5	1.0	30	12	9.8	1.7	20.6	.
	35				14	10.8	1.5			
	40				16	12.0	1.3			
	45				18	13.0	1.1			
	50				20	14.0	1.0			
	60				24	16.5	0.9			
10	NAL 10.6-30	12.8	10.6	1.1	30	12	9.1	1.7	20.6	.
	35				14	9.9	1.5			
	40				16	11.0	1.3			
	45				18	12.1	1.1			
	50				20	12.7	1.0			
	60				24	14.9	0.9			
13	NAL 13.6-35	16.4	13.6	1.4	35	14	12.3	2.0	27.5	.
	40				16	13.3	1.7			
	45				18	14.7	1.5			
	50				20	15.8	1.4			
	60				24	18.2	1.1			
16	NAL 16.6-35	19.8	16.6	1.6	35	14	13.6	2.0	27.5	.
	40				16	14.8	1.7			
	45				18	16.0	1.5			
	50				20	17.2	1.4			
	60				24	20.0	1.1			

- 荷重(N)=定數(N/mm)×壓縮量(mm)
- 密著長是參考值, 製作時會有少許差異
- 1N=0.101972Kg f · 耐熱溫度80°C
- NAL ☑部兩端研磨

訂貨方式:  交期:  天  
NAL5.5-30