



NSWH/NSWSH

止付螺絲



Ma. 材質 S45C
Ha. 硬度 HRC34~43
Tr. 處理 四三酸化鐵被膜



品號 Type	M	M x P	L	B	d	單價		
NSWH (標準型)	12	12x1.5	10	6	3	•		
	14	14x1.5		8		•		
	16	16x1.5		10		•		
	18	18x1.5		12		•		
	20	20x1.5		12		14	5	•
	22	22x1.5				17		•
	24	24x1.5	•					
	25	25x1.5	12	14	5	•		
	26	26x1.5				•		
	27	27x1.5				•		
	28	28x1.5				•		
	30	30x1.5				•		
	33	33x1.5	•					

品號 Type	M-L	M x P	L	B	d	單價			
NSWSH (短型)	12-6	12x1.5	6	6	3	•			
	14-6	14x1.5				•			
	16-6	16x1.5				8	•		
	18-6	18x1.5				10	•		
	20-8	20x1.5				8	14	5	•
	22-8	22x1.5							12
	24-8	24x1.5	•						
	25-8	25x1.5	8	14	5	•			
	26-8	26x1.5				•			
	27-8	27x1.5				•			
	28-8	28x1.5				•			
	30-8	30x1.5				•			
	33-8	33x1.5	17	•					

■ 孔付型

· 空氣及油污可順利從中心孔處排出
 以防止頂料稍作動不良

訂貨方式： 交期：

NSWH12
NSWSH12-6

Ex. 使用例

